


GRID ANTENNA 2400 - 2485 MHz

	Backhaul	Point-to-Point
Features of the 2400 MHz Wire Grid Antenna with arm to mount Motorola Canopy Module	Customer	Premises Equipment
True to Specification Performance - Excellent RF Performance		
Narrow beamwidth to minimize outside interference		
Lowest Windload for extreme, wind, or snow environments		
Zinc plated cold rolled steel with polyester powder coat		
Polyester powder coat L Bracket and Muffler Clamp - SS Hardware		
Heavy Duty Mounting Bracket and Double U Bolt Included		
Engineered for 2.4 GHz Motorola Canopy Modules		
For use with 1" - 2 3/4" Diameter mast/poles (25 - 70 mm)	SPECIFICATIONS	
-45 to +70 Degrees Centigrade Operating Temperatures	Part Number	GAMC2424
Use for ISM, WISP, WiFi, WiMAX Networks - 802.11 Compatible	Frequency Range	2400 - 2485 MHz
	Gain	24 dBi
	Front to Back Ratio	<24 dBc
	Return Loss	10 dB
	Beamwidth	21H 19V Degrees
	VSWR	1.5:1 or less Typical
	Input Impedance	50 Ohms
	Maximum Power	200 Watts
	Connector Interface	N Type
	Windload	210 MPH
	Lightning Protection	Direct Ground
	L X W X H	34"X28"X11"
		863mmX711mmX279mm
	Weight	6 lb/2.7 kg
	Mast Sizes Compatible	1"-2.75" 25mm-70mm
	Grid Antenna includes	wire grid reflector
	arm and	hardware kit
Shipped Direct from Manufacturer		
One Year Warranty, Repair or Replacement, Provided by Manufacturer		www.1wirelessway.com



GAMC2424