

GRID ANTENNA 4900, 5200, 5400, 5700 MHz

**Backhaul Point-to-Point
Customer Premises Equipment**

**Features of the 4.9 - 5.7 GHz Wire Grid Antenna
with arm to mount Motorola Canopy Module**

- True to Specification Performance - Excellent RF Performance
- Narrow beamwidth to minimize outside interference
- Lowest Windload for extreme, wind, or snow environments
- Zinc plated cold rolled steel with polyester powder coat
- Polyester powder coat L Bracket and Muffler Clamp - SS Hardware
- Heavy Duty Mounting Bracket and Double U Bolt Included
- Engineered Specifically for 5 GHz Motorola Canopy Modules



- For use with 1" - 2 1/2" Diameter mast/poles (28 - 64 mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- Use for ISM, WISP, WiFi, WiMAX Networks - 802.11 Compatible

SPECIFICATIONS

Part Number	GAMC24R
Frequency Range	4900 - 5900 MHz
Gain	24 dBi
Front to Back Ratio	<32 dBc
Return Loss	12 dB
Beamwidth	10H11V
VSWR	1.5:1 or less Typical
Input Impedance	50 Ohms
Maximum Power	200 Watts
Polarization	Vertical
Windload	210 MPH
Polarization	Vertical
Lightning Protection	Direct Ground
L X W X H	24"X24"X6"
	609mmX609mmX152mm
Weight	8 lb/3.6 kg
Mast Sizes Compatible	1"-2.5" 28mm-64mm

GAMC24R



Shipped Direct from Manufacturer

Grid Antenna includes passive feed, hardware kit
arm to mount module and wire grid reflector

One Year Warranty, Repair or Replacement, Provided by Manufacturer

www.1wirelessway.com