

## OMNI ANTENNA 2500 - 2686 MHz


### Features of the 2500 MHz Omni Directional Antenna

- True to Specification Performance to Minimize Outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong Aluminum Construction - Waterproof
- Powder Coated Enclosure for Rough Environments
- Vertical Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5"- 2.76" Diameter Mast/Poles/Mounts (40 - 70mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Clamping Hardware System SS Hardware
- Use for 2500 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

OMNI		NLOS
Base Station		None Line of Sight Applications
		
<b>SPECIFICATIONS</b>		
Part Number	OM2509V	
Frequency Range	2500 - 2686 MHz	
Gain	9 dBi	
VSWR	1:5:1 Typical	
Impedance	50 Ohms	
Maximum Power	100 Watts	
Beamwidth	14 E	
PIM	<107	
Structure	UV Res Fiberglass	
Wind Velocity	130 mph/210 kmh	
Mounting Hardware	S/S U Bolt with Muffler Brace	
DC Ground	Photo	may not be exact model
		<a href="http://www.1wirelessway.com">www.1wirelessway.com</a>