

OMNI ANTENNA 710 - 746 MHz


Features of the 700 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside interference
- High Performance Design Eliminates Nulls
- Extra Strong Aluminum Construction - Waterproof
- Powder Coated Enclosure for Rough Environments
- Horizontal Polarization DOCSIS Compatible
- Lifetime Warranty 7/16 DIN Connector
- For use with 1.5" - 3.5" Diameter mast/poles (40 - 90 mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Clamping Hardware System SS Hardware
- Use for 700 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

| | OMNI | NLOS |
|---|----------------------|--|
| | Base Station | None Line of Sight |
|  | | |
| SPECIFICATIONS | | |
| Part Number | OM7006H | |
| Frequency Range | 710 - 746 MHz | |
| Gain | 6 dBi | |
| VSWR | 1:5:1 Typical | |
| Impedance | 50 Ohms | |
| Maximum Power | 250 Watts | |
| Beamwidth | 25 E | |
| PIM | <107 | |
| Structure | Aluminum One Element | |
| Wind Velocity | 130mph/210kmh | |
| | | |
| | | |
| DC Ground | Photo | may not be exact model |
| | | www.1wirelessway.com |