

OMNI ANTENNA 760 - 780 MHz

Features of the 760 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong UV Resistant Fiberglass Construction - Waterproof
- Stainless Steel Base and Stainless Steel Hardware
- Vertical Polarization DOCSIS Compatible
- Lifetime Warranty 7/16 DIN Connector
- For use with 1.57"-2.76" Diameter mast/poles 40-70 mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Muffler Mounting Hardware
- Use for 700 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

OMNI	NLOS
Base Station	None Line of Sight
	
SPECIFICATIONS	
Part Number	OM7606V
Frequency Range	760 - 780 MHz
Gain	6 dBi
VSWR	1:5:1 Typical
Impedance	50 Ohms
Maximum Power	150 Watts
Beamwidth	25 E
PIM	<107
Structure	UV Res Fiberglass
Wind Velocity	130 mph/210 km
DC Ground	Photo may not be exact model
	www.1wirelessway.com