

## OMNI ANTENNA 900 - 930 MHz


### Features of the 900 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside interference
- High Performance Design Eliminates Nulls
- Extra Strong Aluminum Construction - Waterproof
- Powder Coated Enclosure for Rough Environments
- Horizontal Polarization - IEEE 802.11 Compatible
- Lifetime Warranty 7/16 DIN Connector
- For use with 1.5"- 3.5" Diameter mast/poles (40 - 90 mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Clamping Hardware System SS Hardware
- Use for 900 MHz Networks - WISP - ISM - NLOS



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

	OMNI	NLOS
	<b>Base Station</b>	None Line of Sight
		
<b>SPECIFICATIONS</b>		
Part Number	OM90011H	
Frequency Range	900 - 930 MHz	
Gain	11 dBi	
VSWR	1:5:1 Typical	
Impedance	50 Ohms	
Maximum Power	250 Watts	
Beamwidth	8.2 E	
PIM	<107	
Structure	Aluminum One Element	
Wind Velocity	130 mph/210kmh	
DC Ground	Photo	may not be exact model
<a href="http://www.1wirelessway.com">www.1wirelessway.com</a>		