

OMNI ANTENNA 890 - 960 MHz


Features of the 900 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong UV Resistant Fiberglass Construction - Waterproof
- Stainless Steel Base and Stainless Steel Hardware
- Vertical Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5"-2.76" Diameter Mast/Poles (40 - 70mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Muffler Mounting Hardware SS
- Use for 900 MHz Networks - WISP - ISM - NLOS



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

OMNI	NLOS
Base Station	None Line of Sight
	
SPECIFICATIONS	
Part Number	OM9009V
Frequency Range	890 - 960 MHz
Gain	9 dBi
VSWR	1:5:1 Typical
Impedance	50 Ohms
Maximum Power	100 Watts
Beamwidth	13.5 E
PIM	<107
Structure	UV Res Fiberglass
Wind Velocity	130mph/210kmh
DC Ground	Photo
	may not be exact model
	www.1wirelessway.com