

OMNI ANTENNA 930 - 960 MHz

Features of the 930 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong UV Resistant Fiberglass Construction - Waterproof
- Stainless Steel Base and Stainless Steel Hardware
- Vertical Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5"-2.76" Diameter Mast/Poles (40 - 70mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Muffler Mounting Hardware SS
- Use for 900 MHz Networks - WISP - ISM - NLOS



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

	OMNI	NLOS
	Base Station	None Line of Sight
		
SPECIFICATIONS		
Part Number	OM9309V	
Frequency Range	930 - 960 MHz	
Gain	9 dBi	
VSWR	1:5:1 Typical	
Impedance	50 Ohms	
Maximum Power	100 Watts	
Beamwidth	13.5 E	
PIM	<107	
Structure	UV Res Fiberglass	
Wind Velocity	130mph/210kmh	
DC Ground	Photo	may not be exact model
		www.1wirelessway.com