

PANEL - SECTOR ANTENNA 5725 - 5850 MHz

	NLOS	None Line of Site Applications
Features of the 5700 MHz Sector Antenna	BASE STATION	APPLICATIONS
True to Specification Performance for Excellent RF Operation		
Air Dielectric Construction		
Copper Clad PCB for Radiation Elements		
Broadband Dipole Array on Aluminum Extrusion Reflector		
Irridite Treated Aluminum for Reflector		
Powder Coat Finish over Heavy Duty Aluminum		
UV Stabilized Resistant PVC Plastic Radome for Long Life	SPECIFICATIONS	
DC Ground for Lightning Protection	Part Number	PA5712015V
Lifetime Warranty Female N Connector	Frequency Range	5725 - 5850 MHz
Heat Shrink on Recessed Connector for Moisture Control	Gain	15 dBi
Heavy Duty Stainless Steel Scissor Tilt Mounting System	Beamwidth	H90 V8.5
Mechanical Downtilt up to 15 Degrees Adjustable	Front to Back Ratio	>=25
-45 to +70 Degrees Centigrade Operating Temperatures	VSWR	1.5 or less typical
	Rated Wind Velocity	210 km/h 130 m/h
	Maximum Power	250
	Polarization	Vertical
	Input Impedance	50 Ohms
	Construction	Air Dielectric
	Radiation Element	Aluminum Alloy
	Radome Material	UV Resistant PVC
	Mounting Hardware	Steel Tilt Brackets
	Connector Interface	Female N
	Structure	One Panel
	Lightning Protection	Direct Ground
	Mast Sizes Compatible	1.57"-2.36"/40-60 mm
	Mounting Brackets	Polyester Powder Coat
	Mounting Hardware	Stainless Steel Nuts & Bolts
Shipped Direct from Manufacturer	Photo may not be	exact model
One Year Warranty, Repair or Replacement, Provided by Manufacturer		www.1wirelessway.com